



We are the largest lessor of refrigerated containers in the world.

Our equipment is built of the highest quality, zinc coated, corrosion resistant stainless steel that are designed to withstand the most severe and extreme salt-water environments while maintaining its thermal efficiency. Our equipment is also fitted with the latest, most up-to-date technology and machinery which allows easy, continuous monitoring of temperatures and other conditions which are critical to your cargos requirements. Because all our equipment is built to the highest standards in terms of durability and quality, customers who invest in Seacastle equipment benefit from a truly professional aesthetic appearance, longer lease terms, and lower off-hire costs all of which maximize the value of your investment.

Contact Sales

North America San Ramon, CA	1 925 480 3000
South America Brazil	+ 55 41 3302 0730
Asia Pacific Hong Kong Singapore	+ 852 2620 5620 + 65 6372 9900
Europe Netherlands	+ 31 1642 71060

RATING	20' REEFER 20' x 8'-0" x 8'-6"		40' HC Reefer 40' x 8'-0" x 9'-6"	
	kg	lb	kg	lb
Tare Weight including Reefer	2,980	6,570	4,700	10,360
Tare Weight excluding Reefer	2,440	5,380	4,160	9,170
Payload	27,500	60,630	29,300	64,600
MGW	30,480	67,200	34,000	74,960
EXTERNAL DIMENSIONS	mm	ft-in	mm	ft-in
Length	6,058	20'-0"	12,192	40'-0"
Width	2,438	8'-0"	2,438	8'-0"
Height	2,591	8'-6"	2,896	9'-6"
INTERNAL DIMENSIONS	mm	ft-in	mm	ft-in
Length	5,456	17'-10"	11,590	38'-0"
Width	2,294	7'-6"	2,284	7'-5"
Height	2,273	7'-5"	2,545	8'-4"
DOOR OPENING	mm	ft-in	mm	ft-in
Width	2,290	7'-6"	2,290	7'-6"
Height at sill	2,264	7'-5"	2,569	8'-5"
Height - cargo access	2,221	7'-3"	2,502	8'-2"
CUBE	m³	ft³	m³	ft³
Cubic capacity	28.4	1,0	67.4	2,382